

Turbocharged Diesel Engine Modelling for Nonlinear Controller Design

Silvio Simani

Department of Engineering, University of Ferrara

Via Saragat, 1E - 44100 Ferrara (FE) ITALY

Ph: +39 0532 97 4844. Fax: +39 0532 97 4870

URL: www.ing.unife.it/simani

Email: silvio.simani@unife.it

Projects and Research Topics

- *Turbocharged Diesel Engine Modelling for Nonlinear Controller Design (2007-2009)*
- ✓ *Computerised Decision Support Systems for Oral Anticoagulant Treatment (OAT) Dose Management (2005-2007)*
- ✓ *Development of Fault Tolerant NGC (Navigation, Guidance & Control) Algorithms for CUAV (Civil Unmanned Aerial Vehicle) Patrolling & Rescue Missions in Harsh Environment (2004-2008, 2009-2011)*
- ✓ Just started (2009 - 2011):
 - Mobile robots & SLAM - Simultaneous Localization And Mapping
 - Image based visual servoing of robot manipulators - application to robotic surgery

Introduction

✓ Control scheme calibration and tuning for commercial diesel engines (boats, ships, farm tractors, ...)


➤ Diesel engine modelling and identification

- grey-box: analytical approach and identification
- black-box: fuzzy modelling and identification

➤ BOSCH Electronic Control Unit (ECU)

- Controller parameter calibration and tuning
- Automated software tool for 'diesel calibration engineers'

Project Logic Scheme



Project Achievements

- Control-oriented simulation model
 - Grey-box model from real data (test-rig engine system)
 - ✓ Black-box engine model from real data (driving cycles)
- BOSCH controller implementation in Matlab/Simulink environments
- Automatic software (GUI) for controller calibration and parameter tuning

The Diesel Engine and its Emissions



Diesel Usage

- ✓ Nearly all trucks, buses, trains, small ships
 - Good fuel efficiency
 - Lower greenhouse gas emissions
 - Reliability
- ✓ Enormous size range:
 - 30 to 30,000 kW (40 to 40,000 hp)
- ✓ Usage has increased significantly in last 30 years.

Diesel Combustion

- ✓ Combustion: only two exhaust by-products?
 - CO_2 and H_2O
- ✓ Unfortunately...
 - Diesel is not pure carbon and hydrogen:
 - sulphur, nitrogen
 - Air is not pure oxygen
 - nitrogen
- ✓ Engine combustion at high temperature and high pressure: environment to form **many chemical compounds**

Diesel Emissions


- 
- ✓ Particulate Matter (PM)
 - A product of incomplete combustion
 - ✓ Oxides of Nitrogen ($\text{NO} + \text{NO}_2 = \text{NO}_x$)
 - NO_x is a product of high temperature combustion
 - ✓ And other minor compounds...
 - Carbon monoxide, sulphur dioxide (SO_2)

Emission Reduction Strategies


- ✓ Reducing PM
 - Improve combustion efficiency
 - Increase peak combustion temperature
- ✓ Reducing NO_x
 - Reduce peak combustion temperature
- Air-to-Fuel (Mass) Ratio (AFR) Control
 - Computer-controlled fuel and air injection rates
- Exhaust Gas Recirculation (EGR)
 - Combustion temperature reduction

Adjust AFR or AMF

- AFR adjustment
 - Depends on torque
 - Engine speed
- AMF control
 - exploited in this project!



NO_x and PM Control




- 1) **AMF (Air Mass Flow) control**
 - Reference, set point
- 2) Reduce Flame Temperature
 - EGR
 - TVA

Control Objectives

- The control objective is to operate the TVA and EGR valves in a way such that:
 - the engine meets the driver's torque demand
 - NO_x and PM emissions are optimised
 - visible smoke generation is avoided
- This can be achieved by regulating the Air Mass Flow (AMF) and the fraction of exhaust gases in the intake manifold to the corresponding set-points

Set Point Generation



- Air Mass Flow (AMF) set-point is given as function of engine fuelling and speed
- It is computed to give minimum NO_x and PM emissions without any visible smoke
- In steady-state, AMF (and exhaust gas fraction) can be correlated to the engine outputs (e.g. compressor mass flow and exhaust manifold pressure) through thermodynamic relationships (maps)

Control-Oriented Diesel Engine Modelling



Diesel Engine Modelling

- Process description and modelling
 - 1. Grey-box approach
 - Engine maps and look-up tables
 - Engine subsystems and components
 - 2. Black-box approach
 - Fuzzy modelling and identification
- Model Validation



Diesel Engine Scheme



Inputs



- Engine speed (N)
- Fuel flow rate (w_{fuel})
- Intake Temperature
- Engine Temperature

Input Control Variables

- EGR command
- TVA command

Main Output

- Air Mass Flow AMF (w_{c1})



**Diesel Engine
Grey-Box Modelling**

MATLAB® /SIMULINK® Library

- Control-oriented engine simulation model
- MATLAB® / SIMULINK® environments
- Easy to use
- Reduced simulation time
- Control design, test, performance assessment
- Controller calibration and final tuning
- Real-time applications

System Modelling

✓ State parameters

- P, T, ρ , c, W, ...
- N (speed)
- X (chemical composition)
- ...

✓ Variables

- ...

✓ Equations


- Mass conservation
- Energy conservation
- Momentum conservation
- Motion quantity conservation
- State equations
- Transformation equations

Components and Fluid-Dynamics

- ✓ Fluid machines (work exchange, $\Pi \neq 0$ & $\Phi = 0$)
- ✓ Restrictions (no energy exchange, $\Pi = 0$ & $\Phi = 0$)
- ✓ Heat exchangers & combustion chambers
(thermal exchange, $\Pi = 0$ & $\Phi \neq 0$)
- ✓ In-Cylinder Processes (thermal & work exchange,
 $\Pi \neq 0$ & $\Phi \neq 0$)

Exhaust Gas Recirculation (EGR)

➤ Valves & Restrictions



- ✓ Compressible Isentropic flow + flow coefficient C_d

EGR – Algebraic Equations

Output

$$\dot{m} = \frac{C_d A(p_0)_{in}}{\sqrt{R(T_0)_{in}}} \cdot \left(\frac{p_{out}}{(p_0)_{in}} \right)^{\frac{1}{k}} \cdot \sqrt{\frac{2k}{k-1} \left[1 - \left(\frac{p_{out}}{(p_0)_{in}} \right)^{\frac{k-1}{k}} \right]}$$

Input

$$\text{where } \left(\frac{p_{out}}{(p_0)_{in}} \right) > \left(\frac{2}{k+1} \right)^{\frac{k}{k-1}}$$

$$\dot{m} = \frac{C_d A(p_0)_{in}}{\sqrt{R(T_0)_{in}}} \cdot \sqrt{k} \cdot \sqrt{\left(\frac{2}{k+1} \right)^{\frac{k+1}{k-1}}}$$

$$\text{where } \left(\frac{p_{out}}{(p_0)_{in}} \right) \leq \left(\frac{2}{k+1} \right)^{\frac{k}{k-1}}$$

Note: grey-box approach

Throttle Valve Actuator (TVA)



$$w_{th} = \begin{cases} \frac{k A_{th}(\alpha, N) p_{amb}}{\sqrt{RT_{up}}} \left(\frac{p_{th}}{p_{amb}} \right)^{1/\gamma} \sqrt{\frac{2\gamma}{\gamma-1} \left(1 - \left(\frac{p_{th}}{p_{amb}} \right)^{\frac{\gamma-1}{\gamma}} \right)} & \frac{p_{th}}{p_{amb}} > \bar{p} \\ \frac{k A_{th}(\alpha, N) p_{amb}}{\sqrt{RT_{up}}} \sqrt{\gamma} \left(\frac{2}{\gamma+1} \right)^{\frac{\gamma+1}{2(\gamma-1)}} & \frac{p_{th}}{p_{amb}} \leq \bar{p} \end{cases} \quad (1)$$

Algebraic Model

- w_{th} is the flow through throttle
- From experimental data, the parameters k and A_{th} (α) have to be *identified* (also as function of N)
 - Maps (look-up tables) or polynomials
- It is assumed that the downstream pressure p_{th} (unknown) $p_{th}=p_{man}$


Valve SIMULINK® Blocks

■ Valves and restrictions: examples



Control of the vacuum generator PWM and not the valve lift!

Manifold SIMULINK® Blocks




Turbocharger (Turbine - Compressor)

➤ *Intake manifold*

➤ *Exhaust manifold*

➤ *Turbocharger*



Engine Modelling Issues

➤ **Engine subsystems contain unknown terms:**

- Effective area (valves & restrictions, i.e. EGR/TVA):
 $A_{EGR}(x_{EGR})$, $A_{TVA}(x_{TVA})$
- Volumetric efficiency (cylinder): $\eta_v(N_e, P_{im})$
- Compressor/turbine isentropic efficiencies:
 $\eta_c(N_{tc}, T_{amb}, P_{im}/P_{amb})$, $\eta_t(x_{VGT}, N_{tc}, T_{em}, P_{out}/P_{em})$
- Engine temperature: $f(N_e, W_f)$

➤ **Modelled by:**

- Maps (1-D & 2-D) or polynomials

... about 1 year

Engine Complete Description

➤ Engine Sub-models


- ✓ EGR
- ✓ TVA
- ✓ IM/EM
- ✓ Cylinders: Volumetric efficiency
- Turbine + Compressor: flow & efficiency maps
- ✓ Coolers: efficiency parameters

□ Model Validation

- To be completed



Engine Complete Description (Cont'd)



Diesel Engine *Black-Box* *Fuzzy Modelling*



Fuzzy Modelling - FMID™

➤ Brief review

- Nonlinear regression and black-box modelling can be based on the partitioning data into *clusters*
- A cluster is a set of objects that are more similar to each other than to objects from other clusters

FMID – Problem Formulation

- Given is a set of data
- Find the partitioning of the data into subsets (clusters), such that samples within a subset are more ‘similar’ to each other than to samples from other subsets
- Similarity is mathematically formulated by using a distance measure

Fuzzy Clustering and Rules


Takagi-Sugeno system
(one model for each cluster i)

$$y = a_i x + b_i$$

Rule-based description

If x is A_1 then $y = a_1 x + b_1$
 If x is A_2 then $y = a_2 x + b_2$
 If x is A_3 then $y = a_3 x + b_3$
 If x is A_4 then $y = a_4 x + b_4$

Global fuzzy model: $\sum_{i=1}^c \mu(x)(a_i x + b_i)$



Diesel Engine Application

➤ Input-output data

- Engine fuelling
- Engine temperature
- Intake temperature
- Engine speed
- EGR command
- TVA command

- AMF output signal

$$\text{Fuzzy model: } y(t) = \sum_{i=1}^c \mu(x(t))(a_i x(t) + b_i)$$


(4+2) Inputs (x)

1 Output (y)


... few weeks

➤ FMID™ for MATLAB® by Prof. Robert Babuska (Delft, The Netherlands). URL: <http://www.dcs.tudelft.nl/~babuska/>

Identified Fuzzy Model FMID™




- Local models' order: $n = 2$
- Cluster number: $c = 9$




Note:
 c & n optimised
 via a PEM
 iterative scheme

Fuzzy Model Simulation


- Fuzzy model simulation
- Good performances for validation and several test data sequences
- Best fit > 75% (in simulation & validation)



Fuzzy Model Simulation (zoom)




Local Submodels (9 ARX models)



BOSCH Controller 'Strategy' and Parameter Tuning




Control Model Simulation



- ✓ Specific set-point assigned depending on fuel demand (W_f) and speed (N).
- ✓ The controller actuates the EGR and TVA valves to correct the deviation between actual (AMF) and demanded variable

Calibration in SIMULINK®



BOSCH Controller Strategy


Adaptive gains

FF: depends of fuel & RPM. Based on AMF static map inversion


Gain scheduler

Integrator
reset logic

EGR/TVA
split




Parameter Adaptation (Gain Adapt)



- BOSCH controller's main idea is to correct the PI gains (K_i & K_p) on the basis of the error value and precompiled static maps
- Depends on engine fuelling, RPM, asp. temp and tracking error (actual and desired MAF)
- Fixed thresholds (KiPOS & KiNEG)

Gain Scheduler: 'PI' Params



- It multiplies P & I gains and parameters
- Example:

$$P = \begin{cases} K_p^{(\text{scheduled})} \times e & \text{if } |e| < e_{\max} \\ K_p^{(\text{scheduled})} \times e_{\max} + K_{p,\max} \times (e - e_{\max}) & \text{otherwise} \end{cases}$$

- 'Bumpless' strategy

BOSCH Controller Calibration Strategy




Driving Cicle Prototype...



CONFIDENTIAL: Prototype 2009 HD truck – field test unit


Complete System (EU Driving Cycle)



Technology


- Diesel engine driving cycle data
- MATLAB®/SIMULINK® interface
 - Calibration, optimisation; model, controller analysis, simulation and design
- ATI VISION™
 - Integrated calibration measurement solution for accessing ECUs
 - Table calibration
 - Memory emulation (μ -controller)
 - On target rapid prototyping

Parameter Correction




- Matlab/Simulink
 - ❖ Parameter Estimation Toolbox
 - Optimisation Toolbox
 - Pattern Search and Genetic Algorithm
- PEM algorithm
- MAF tracking optimisation
- Final validation

GUI: The Final Interface



- The user can select:
 - Data
 - Parameters
 - Optimisation algorithms
- The GUI tool ‘suggests’ the controller params & maps

Parameter Correction (Example)




=

(Nominal Map, IC)


=

(Controller Tuned Final Map)


Map Correction (Example)



(provided by
BOSCH)




(the map to
be tuned)



Final controller map


Parameter Estimation Toolbox
and Genetic Algorithm

Controller Structure & Params



- ✓ Pre-control:
1 map
- ✓ Gain adapt:
2 maps
- ✓ P : 5 real
variables
- ✓ I : 5 real
variables

Simulation Results (EU Driving Cycle)



Alternative Procedures

- Related HD diesel engine control literature:
 - Model-based predictive controller
 - Fuzzy controller
 - Neural networks
 - ✓ Adaptive controllers

Conclusion

- ✓ TVA/EGR control design
- ✓ Application of the existent control law (BOSCH) to the identified engine model
 - Black-box modelling (fuzzy system)
- ✓ Identified system and controller integration
 - EU Driving cycle data
 - Controller parameter tuning/optimisation
- Matlab/Simulink GUI interface
 - Automated calibration software tool for ‘diesel calibration engineers’
 - ECU calibration and final tuning enhancement

Further Investigations

- Validation of the complete model of a multi-cylinder diesel engine
 - Turbocharger and related maps (grey-box)
- Control law implementation for the complete dynamic model
 - Control law with the real engine
 - Comparison with different control strategies (e.g. adaptive schemes)

References

- *Introduction to Modeling and Control of Internal Combustion Engine Systems* by Lino Guzzella and Christopher H. Onder. Springer, August 2004. ISBN-10: 354022274X. ISBN-13: 978-3540222743.
- Control of diesel engines, by Guzzella, L.; Amstutz, A., *IEEE Control Systems Magazine*, Volume 18, Issue 5, Oct. 1998 Pages: 53 – 71.
- Modeling and Control of Turbocharged SI and DI Engines, by L. Eriksson. In: *Oil & Gas Science and Technology - Rev. IFP*. DOI: 10.2516/ogst:2007042

FOR MORE INFO...

Visit the web page:

www.ing.unife.it/simani/nlw2009.html

Thank you for your attention!

We are well behind and still have a long way to go...

